



SHOWA 3416

The 3416 highly cut-resistant gloves are approved to standards ANSI Level A5 and EN 388 Cut Level 5. As well as preventing injury, these gloves feature a seamless knit to prevent skin irritation over long periods of wear, and a rough outer surface for increased grip and tactile precision. These gloves are also resistant to acids, chemicals, solvents, and oils, to keep hands safe from harmful substances.



BENEFITS

- Cut-resistant
- Seamless knit
- Acid-resistant
- Flexible
- Extra Grip
- · Increased dexterity

FEATURES

- Rough grip
- · Fully-coated neoprene
- Strong chemical resistance
- Cut-resistance

INDUSTRIES



Chemical



Mining



Oil And Gas

HAZARDS



Chemical



Cut

NORMS & CERTIFICATES

Cat II

CE

EN 388:2016+A1:2018



3X43E

EN ISO 374-1:2016+A1:2018/Type

AJKLMT

EN ISO 374-5:2016



TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Handling glass and windows
- Window manufacturing
- Handling heavy equipment
- Drilling
- Deck crew





PACKAGING

- Pair per polybag: 12
- Polybags per case: 6
- Pair per case: 72

LENGTH

355 mm

COATING

Neoprene

LINERS

- Cut resistant HPPE
- Knit weight Mediumweight

SIZES

8/S | 9/M | 10/L | 11/XL

COLOUR

Black

MATERIAL

- Engineered yarn
- Seamless knit

GRIP

Rough

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.