

SHOWA 892

Forged with fluoroelastomer rubber, the SHOWA 892 chemical resistant glove provides superior resistance to aliphatic, aromatic and halogenated hydrocarbons, such as Benzene, Toulene, and Xylene, Methylene chloride, etc. The butyl rubber coating is designed against highly corrosive acids, ketones, esters, alcohols.



BENEFITS

- Acid-resistant
- Hydrocarbon-resistant
- Impermeable

FEATURES

- Unlined Viton®
- Butyl rubber
- Smooth grip
- Unsupported

NORMS & CERTIFICATES

Cat III



2777

EN ISO 374-1:2016+A1:2018/Type A



ABCDJLMNPST

EN ISO 374-5:2016



VIRUS



INDUSTRIES



Chemical

HAZARDS



Chemical

TRADES & APPLICATIONS

- Chemical spray and treatment
- Coating preparation
- Laboratory, pharma & analysis
- Painting & spray workshops
- Fracking
- Drilling

GET IN TOUCH

SHOWA International | WTC - Tower 2 - Strawinskyiaan 1077 XX Amsterdam - The Netherlands

showagroup.com | info@showagroup.eu

© SHOWA GROUP 2024 | All rights reserved

PACKAGING

- Pair per polybag: 12
- Polybags per case: 1
- Pair per case: 12

THICKNESS

0.30 mm

LENGTH

300 mm

COATING

- Viton

SIZES

7/S | 8/M | 9/L | 10/XL | 11/XXL

COLOUR

- Black

MATERIAL

- Unsupported

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

GET IN TOUCH

SHOWA International | WTC - Tower 2 - Strawinskyiaan 1077 XX Amsterdam - The Netherlands
showagroup.com | info@showagroup.eu
© SHOWA GROUP 2024 | All rights reserved