

SHOWA 8814

The SHOWA 8814 heat-resistant gloves are designed to withstand temperatures up to 500°F/260°C for 15 seconds. Even after multiple washings, the 8814 maintains its heat-protective qualities. The textured surface of the neoprene coating provides superior tactile dexterity. When working in dry heat environments, this glove keeps your hands protected. Easy donning and doffing makes the glove easy to remove in an emergency.



BENEFITS

- Machine washable
- Increased dexterity
- Easy donning and doffing
- Heat-resistant

FEATURES

- Rough grip
- Spray Coated Neoprene

NORMS & CERTIFICATES

Cat II



EN 388:2016+A1:2018



1242X

EN 407:2020



X2XXXX

Food Contact



INDUSTRIES



Food



Mining

HAZARDS



Heat

TRADES & APPLICATIONS

- Automotive repairs and maintenance
- Mechanical and engineering
- Metal Stamping
- Bakeries & delicatessens
- Casting

GET IN TOUCH

SHOWA International | 579 Edison Street, Menlo, GA 30731, USA | showagroup.com |

USA@SHOWAGroup.com

© SHOWA GROUP 2024 | All rights reserved

PACKAGING

- Pair per case: 12

LENGTH

14 in. (355 mm)

COATING

- Neoprene

SIZES

7/S | 8/M | 9/L | 10/XL

COLOUR

- Black

MATERIAL

- Cotton
- Cut and sewn
- Polyester

USER INSTRUCTIONS

Gloves provide protection from chemical and mechanical hazards shown. Do not use gloves that show signs of wear. If required, cleanse outer surface of glove with running water. Discard used gloves in compliance with local regulations. Do not wear gloves when there is a risk of entanglement by moving parts of machines.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

GET IN TOUCH

SHOWA International | 579 Edison Street, Menlo, GA 30731, USA | showagroup.com | USA@SHOWAGroup.com
© SHOWA GROUP 2024 | All rights reserved